

CAMINHÃO GUINDASTE TODO TERRENO

QAY220

Tabela de Cargas - Lança Principal (Contrapeso 65t) - Patola totalmente estendida 8,7m, operação com 360°

Comp. da lança	13.6m	18.2m	18.2m	18.2m	22.9m	22.9m	22.9m	27.5m	27.5m	27.5m	32.1m	32.1m	32.1m	36.8m	36.8m	36.8m	41.4m	41.4m	41.4m	46.1m	46.1m	46.1m	50.7m	50.7m	50.7m	55.3m	55.3m	55.3m	60m	64m	
R. de Trabalho (m)	Capacidade de levantamento (t)																														
3	220.0																														
3.5	160.0	150.0	145.0	125.0																											
4	145.0	140.0	140.0	117.0	115.0	130.0	110.0																								
4.5	135.0	130.0	130.0	110.5	108.0	122.5	104.5	103.5	115.0	103																					
5	125.0	125.0	120.0	1040	102.0	115.5	99.5	98.0	110.0	98	89	95	64.5	79	79	73															
6	116.0	113.0	112.5	94.0	91.0	102.0	91.0	87.0	103.0	88.5	79.5	92.5	61	72	72.5	69.5															
7	102.7	101.0	102.0	85.0	81.9	91.0	83.5	78.0	93.0	81	73	85.4	57	65	66	66	56	56.5	60												
8	89.5	89.0	89.7	78.0	74.0	82.5	76.5	70.9	84.5	74.5	66	79	54	59	60.5	62.5	52	52	55	48	48.5	39.5									
9	79.0	78.5	79.2	72.0	67.9	74.9	70.0	64.5	77.5	69	60	72.9	51.5	54	55.5	60	47.5	47.5	50	44.5	45.5	37.5	40	40	34.5						
10	67.0	70.0	70.9	67.0	62.5	68.5	64.5	59.9	71.0	64	55	67	49	46	47	49.5	43.7	44	46	41.4	43	35.4	37.5	37.5	33.5	32.5	33	29.5			
12		56.7	57.7	58.3	55.0	57.1	56.0	51.0	57.8	56.5	47	58	44.5	40	43.9	43.5	39.5	37.5	39.5	35.4	37	31.4	32	33.5	31	29.3	29.5	28	25.2		
14		46.7	47.7	48.5	46.2	47.2	48.5	44.5	47.8	49.3	40	48.7	41.5	35.4	38.5	40.4	34.5	36.5	35	31.5	32.4	27.5	28	30	27.5	27	27.5	26	23.5	21.3	
16					38.8	39.7	41.1	39.2	40.5	42	35.5	41.3	38.5	31.5	34	36.5	30.5	32	31	27.5	28.5	24.5	24.5	26	24.5	24.5	25	23	22	19	
18					33.2	34.1	35.3	33.6	34.7	36.2	31.5	35.7	35.5	28	30.1	31.8	26.5	28.5	27.9	24.5	25	22	22	23.5	22	20.9	22.6	21	20.3	17	
20								28.3	29.8	31.5	28.5	30.8	32.5	25	25.8	27.5	23.9	25.5	25	22	23	20	20	22	20	20	20.6	18.9	19	15.3	
22								24.1	25.6	27.1	24.5	26.5	28.1	21.8	22.5	24.1	21.9	23	22.5	19.9	20.5	18	18.9	20.5	18	18.3	18.8	17.1	17.1	13.8	
24											21.1	23.1	24.8	19	19.6	21.3	19.5	21	20.9	18	19	16.5	17.5	17.5	16.5	16.8	17.2	16	16	12.6	
26											18	20	21.8				17.5	19	19	16	17	15	16	16	15	15.4	15.7	13.7	14.9	11.6	
28														14.6	15.4	16.8	16	17.3	18	14.5	15.5	14	14.5	14.9	14	13.8	14.3	13.3	13.9	10.6	
30																	15	15.4	16.3	13.5	14.5	13	13.5	13.5	13	13.2	13.6	12.3	13	9.7	
32																	13.5	13.8	14.5	12.5	13.5	12	12	12.5	12.5	11.9	12.3	11.6	12	8.9	
34																	12	12.3	13	11.5	12.5	11	11.5	11.4	11.4	11.4	11.5	10.8	11	8.2	
36																				10.5	11.5	10.5	10.5	10.9	10	10.5	10.8	10.3	10.4	7.5	
38																				9.3	10.3	9.2				9.7	9.9	9.8	9.5	7	
40																							9.3	9.4	9.7	9	9.2	9.3	9.2	6.6	
42																							8.6	8.8	9.2	8.4	8.6	8.8	8.5	6.1	
44																										7.9	8	8	5.7		
46																										7.3	7.5	7.6	7.5	5.3	
48																													7	4.9	
50																														6.7	4.6
52																														6.5	4.3
54																															4.1
56																															3.8
Nºde linhas	16	15	15	15	12	12	12	11	11	11	9	9	9	7	7	7	6	6	6	5	5	5	4	4	4	3	3	3	3	2	
Área de ângulo	30.8° 73.3°	31.5° 76.8°	31.5° 76.8°	31.5° 76.8°	32.0° 79.0°	32.0° 79.0°	32.0° 79.0°	32.4° 80.5°	32.4° 80.5°	32.4° 80.5°	32.4° 80.5°	32.4° 80.5°	32.4° 80.5°	32.7° 81.6°	32.7° 81.6°	32.7° 81.6°	33.4° 81.9°	33.4° 81.9°	33.4° 81.9°	33.7° 82°	33.7° 82°	33.7° 82°	33.7° 82°	33.7° 82°	33.7° 82°	34.3° 82°	34.3° 82°	34.3° 82°	34.6° 81.6°	29.7° 80.8°	
Moitão	160t							100t							65t							30t									
Peso do Moitão	2416Kg							1543Kg							1001Kg							447Kg									

Tabela de Cargas - Lança Auxiliar JIB (Contrapeso 65t) - Patola totalmente estendida 8,7m, operação com360°, JIB-36m

Comprimento da lança	46.1m			50.7m			55.3m			60m		
Ângulo da Lança	0°	15°	30°	0°	15°	30°	0°	15°	30°	0°	15°	30°
82	4	2.6	2	4	2.6	2	3.7	2.6	2	3.7	2.6	1.8
80	3.6	2.3	1.8	3.6	2.3	1.8	3.6	2.3	1.8	3.6	2.3	1.8
78	3.3	2.3	1.8	3.3	2.3	1.8	3.3	2.2	1.8	3.2	2.2	1.8
76	3.2	2.2	1.8	3.2	2.2	1.8	3	2.2	1.8	3	2.2	1.8
74	3	2.2	1.8	3	2.2	1.6	2.7	2	1.6	2.7	2	1.6
72	2.7	2	1.6	2.7	2	1.6	2.7	2	1.6	2.7	2	1.6
70	2.6	2	1.6	2.6	2	1.6	2.6	2	1.6	2.6	2	1.6
68	2.6	2	1.6	2.3	1.8	1.6	2.3	1.8	1.6	2.3	1.8	1.6
66	2.3	1.8	1.6	2.3	1.8	1.6	2.3	1.8	1.6	2.3	1.8	1.6
64	2.2	1.8	1.6	2.2	1.8	1.6	2.2	1.8	1.3	2.2	1.8	1.3
62	2.2	1.8	1.3	2.2	1.8	1.3	2.2	1.6	1.3	2.2	1.6	1.3
60	2.2	1.6	1.3	2	1.6	1.3	2	1.6	1.3	2	1.6	1.3
58	2	1.6	1.3	2	1.6	1.3	2	1.6	1.3	2	1.6	1.3
56	2	1.6	1.3	2	1.6	1.3	1.8	1.6	1.3	1.8	1.6	1.3
54	1.8	1.6	1.3	1.8	1.6	1.3	1.8	1.6	1.3	1.8	1.6	1.3
52	1.8	1.6	1.3	1.8	1.6	1.3	1.8	1.3	1.3	1.8	1.3	1.3
50	1.8	1.3	1.3	1.8	1.3	1.3	1.6	1.3	1.3	1.6	1.3	1.3
48	1.8	1.3	1.3	1.6	1.3	1.3	1.6	1.3	1.3	1.6	1.3	1.3
46	1.6	1.3	1.3	1.6	1.3	1.3	1.6	1.3	1.3	1.6	1.3	1.3

Comprimento x Largura x Altura (mm)		15850 x 3000 x 3975
Motor	Fabricante/Modelo	DAIMLER AG/ OM502LA.E3A/3
	Potência (kW/rpm)	420/1800
	Torque máximo (N.m/rpm)	2700/1300